

DIMENSIONS

Bushing Cylinder



The dimensions you will find below are standard in the industry and available at Cusson Hydraulique.

EXAMPLE

2" x 4" x 1-1/4" (12" cc)

2" = internal tube diameter

4" = stroke length

1-1/4" = pin diameter

(12" cc) = center and closed-center cylinder

2"

2" x 4" x 1-1/4" (12" cc)
2" x 6" x 1-1/4" (14" cc)
2" x 8" x 1-1/4" (16" cc)
2" x 10" x 1-1/4" (18" cc)
2" x 12" x 1-1/4" (20" cc)
2" x 16" x 1-1/4" (24" cc)
2" x 18" x 1-1/4" (26" cc)
2" x 20" x 1-1/4" (28" cc)
2" x 24" x 1-1/4" (32" cc)
2" x 30" x 1-1/4" (38" cc)
2" x 36" x 1-1/4" (44" cc)

2 1/2"

2-1/2" x 6" x 1-1/2" (14" cc)
2-1/2" x 8" x 1-1/2" (16" cc)
2-1/2" x 10" x 1-1/2" (18" cc)
2-1/2" x 12" x 1-1/2" (20" cc)
2-1/2" x 16" x 1-1/2" (24" cc)
2-1/2" x 18" x 1-1/2" (26" cc)
2-1/2" x 20" x 1-1/2" (28" cc)
2-1/2" x 24" x 1-1/2" (32" cc)
2-1/2" x 30" x 1-1/2" (38" cc)
2-1/2" x 36" x 1-1/2" (44" cc)

3"

3" x 8" x 1-1/2" (16" cc)
3" x 10" x 1-1/2" (18" cc)
3" x 12" x 1-1/2" (20" cc)
3" x 16" x 1-1/2" (24" cc)
3" x 18" x 1-1/2" (26" cc)
3" x 20" x 1-1/2" (28" cc)
3" x 24" x 1-1/2" (32" cc)
3" x 30" x 1-1/2" (38" cc)
3" x 30" x 1-3/4" (38" cc)
3" x 36" x 1-3/4" (44" cc)

3 1/2"

3-1/2" x 8" x 1-3/4" (16" cc)
3-1/2" x 10" x 1-3/4" (18" cc)
3-1/2" x 12" x 1-3/4" (20" cc)
3-1/2" x 16" x 1-3/4" (24" cc)
3-1/2" x 18" x 1-3/4" (26" cc)
3-1/2" x 20" x 1-3/4" (28" cc)
3-1/2" x 24" x 1-3/4" (32" cc)
3-1/2" x 30" x 2" (38" cc)
3-1/2" x 36" x 2" (44" cc)

4"

4" x 8" x 2" (17" cc)
4" x 10" x 2" (19" cc)
4" x 12" x 2" (21" cc)
4" x 16" x 2" (25" cc)
4" x 18" x 2" (27" cc)
4" x 20" x 2" (29" cc)
4" x 24" x 2" (33" cc)
4" x 30" x 2" (39" cc)
4" x 36" x 2" (45" cc)